



# PMC-GBIT-DT2BP

PMC with Dual 1000BaseT/100BaseTX/10BaseT Rear Panel Gigabit Ethernet Interfaces

## Features

- Dual 10BaseT/100BaseTX/1000BaseT network interface card with rear panel access
- Single-wide 32/64-bit 33/66 MHz PCI, 66/133 MHz PCI-X PMC
- Auto-negotiating protocol selection
- Transmit and receive FIFOs
- Drivers for VxWorks®, Linux®, Windows® NT and Windows 2000 available
- Supports Jumbo frames
- Rear panel access provided by the PIM-GBIT-DT module; module has two RJ-45 connectors and LED indicators for link, speed and activity

PMC-GBIT-DT2BP is a PCI Mezzanine Card (PMC) with dual 1000BaseT Gigabit Ethernet interface controller ports and rear panel access.

The Ethernet network interface complies with the IEEE 802.3 specifications for 10BaseT, 100BaseTX, and 1000BaseT over category 5 twisted-pair cable. Full-duplex and half-duplex modes are supported for 10BaseT and 100BaseTX. 1000BaseT supports full duplex mode only. The PMC-GBIT-DT2BP is compliant with standard single-wide PMC IEEE P1386.1, PCI 2.2, and PCI-X 1.0 specifications.

Using the Intel 82546EB with 64KB FIFO buffer memory, the PMC-GBIT-DT2CC allows back-to-back transmissions with minimum interface latency. It also features a 10BaseT, 100BaseTX, and 1000BaseT auto-detection CSMA/CD

interface controller. Dual integrated low-powered MAC/PHY functionality is provided by the Intel 82546EB. The 82546EB appears on the PCI bus as multifunction device, eliminating one PCI-to-PCI bridge and, consequently, significantly improving bus performance. It supports a number of sophisticated features, including auto-negotiation, collision detection, link detection, 4B/5B encoding/decoding (100BaseTX), flow control, and half-duplex/full-duplex. Standard network connection is accomplished through a rear panel I/O connector and rear panel interface module for Ethernet, PIM-GBIT-DT.

The PMC-GBIT-DT2BP addresses applications requiring high-bandwidth system interconnection and PMC form factor.

# PMC-GBIT-DT2BP PMC with Dual Gigabit Ethernet Interfaces

## Specifications

### Technical Highlights

- Single-wide PMC; two ports
- 64-bit PMC Specification IEEE P1386.1 compliant
- Intel® 82546EB PCI Controller/Ethernet MAC
- Protocols: Ethernet 10BaseT, 100BaseTX, 1000BaseT
- Transmit/receive FIFOs with 64 KB total

### PCI Interface

- 32/64-bit, 33/66 MHz, master and slave, 3.3V/5V signaling
- PCI Protocol and Electrical Rev. 2.2
- 66/133 MHz PCI-X bus
- PCI-X 1.0 specification

### Rear Panel I/O Access

- P4

### Rear Panel Access

- Via PIM-GBIT-DT module

### Power Requirements

- +3.3 VDC at 1.6 A (typical)

### Temperature

- Operating: 0° to +55° C
- Storage: -40° to +85° C

### Relative Humidity

- 5% to 95% non-condensing

### Weight

- 0.07 kg (0.16 lbs)

### Dimensions

- 74.0 mm x 143.75 mm

## Ordering Information

### PMC-GBIT-DT2BP

PMC with two copper rear panel Gigabit Ethernet interfaces

### PIM-GBIT-DT

Two port 10/100/1000BaseT rear panel interface module for Gigabit Ethernet PMC-GBIT-DT2CC and PMC-GBIT-DT2BP

### PP-600

Dual PIM carrier for 6U CompactPCI; 100 ohm differential pairs for rear panel Gigabit Ethernet interface

## Note

To assure error-free operation using full-length cable as specified in IEEE 802.3, physical link traces for Gigabit Ethernet signals on all interconnects between the PMC and cable must be routed differentially with 100-ohm differential impedance.

GE Fanuc Intelligent Platforms' PIM carrier PP-600 has matching differential pairs and is recommended to be used with PMC-GBIT-DT2BP and PIM-GBIT-DT.

## About GE Fanuc Intelligent Platforms

GE Fanuc Intelligent Platforms is a leading global provider of embedded computing solutions for a wide range of industries and applications. Our comprehensive product offering includes many types of I/O, single board computers, high performance signal processors, fully integrated, rugged systems including flat panel displays, plus high speed networking and communications products. The company is headquartered in the U.S. and has design, manufacturing and support offices throughout the world. Whether you're looking for one of our standard products or a fully custom solution, GE Fanuc Intelligent Platforms has the breadth, experience and 24/7 support to deliver what you need. For more information, visit [www.gefanuc.com](http://www.gefanuc.com).

## GE Fanuc Intelligent Platforms Information Centers

Americas:  
1 800 322 3616 or 1 256 880 0444

Asia Pacific:  
+81 3 5544 3973

Europe, Middle East and Africa:  
Germany: +49 821 5034-0  
UK: +44 1327 359444

## Additional Resources

For more information, please visit the GE Fanuc Intelligent Platforms web site at:

[www.gefanuc.com](http://www.gefanuc.com)

